Technical Data Sheet



Burdett's Tynong Toppings

Burdett's Tynong Toppings are a light-brown to grey aggregate with a variety of earthy tones.

It is a suitable substitute for Granitic Sand / Gravel.

Tynong Toppings can be used for driveways and pathways; with suitable compaction (e.g. vibrating plate) it will provide a firm base.

Tynong Toppings should ideally be placed at a depth of 50 – 75 mm over an equivalent thickness of solid base such as crushed rock.

Note: Colour and sizing may vary as this is a natural product.

As delivered	After rain or washing

Nominal sizing: 10 – 20 mm

Note: Tynong Toppings as delivered will typically have a thin coating of dust which can initially detract from the product's appearance. This will naturally wash away in time or can be easily removed by spraying with a garden hose.

Top Dressing Sand is available in bulk ex-bin or delivered.

Please contact sales for detailed information on availability and pricing.

May-23

IMPORTANT NOTICE: Above information is based on past test results and experience and is provided in good faith for assessment purposes only. This does not constitute a warranty made by any of the members of the Burdett Group. As Burdett's has no influence on the way in which these products are handled and used, we do not take any responsibility in this respect. You cannot rely solely upon this information to determine appropriate product use and must engage suitably qualified consultants to advise whether the product is fit for your end use.